



How to Install the Lo Pro Mooring cover



Instructions:

***** Snap each of the mooring cover snaps to the snap screw after installing each one.**

***** Please note that if you are replacing a mooring cover the current snaps may not line up with the new cover. May need to install more.**

1. Open up the mooring cover and lay the cover over the boat matching the corners up. (There is a Paddle King tag on the front (bow) center of the mooring cover)
2. Velcro the pockets around the canopy support arms and make sure they are centered.
3. Start at the front center of the boat by placing the notch in the cover around the winch u-bolt used for trailering.



Created On: 09/17/2025



4. Start installing the first self-drilling screw under the first line on the trim on both sides of the u-bolt. (Make sure the self-drilling screws are in line with the mooring cover snaps.)



*** Don't forget to snap the mooring cover to the boat after each screw stud is installed.

5. Install the screw studs on each corner of the bow of the boat to align with the mooring cover snaps and placement of the two center screws. (Under the first line on the trim)
6. Install the remaining screw studs on the front (bow) trim of the boat.
7. Put clamps on the rear corners of the stern to hold the cover in place.
8. Align the snap on the cover to the bottom rail on the stern of the boat.
9. Install the screw studs on each corner on the stern of the boat.
10. Install the center screw stud on the rear of the boat and one screw stud on each side in between the center and corner snaps.



Created On: 09/17/2025



Created On: 09/17/2025

7110 S Crystal Rd, Carson City, MI 48811

989-235-6776



11. Once the bow and stern of the boat are complete, start at the front of the side rails on the port and starboard sides and work your way to the stern of the boat making sure that the screw studs are aligning with the existing snaps on the mooring cover.



Fitting the Lo Pro Mooring Cover with the Poles:

1. Once the cover is installed on the boat and snapped, unsnap a couple of the front snaps.
2. Crawl into the boat and place the mooring poles in the black vents. Adjust the poles so the mooring cover is tight.
3. Crawl back out and snap the front snaps to ensure the cover fits tightly overall.

Maintenance:

Never store the mooring cover when it is wet or damp. Periodically clean and treat your cover. Remove any dirt and dust by brushing the cover with a soft bristle brush, then wet article and scrub using a mild soap. Never use bleach or harsh detergents. 303 is a great brand to clean and protect the cover with. Lubricate snaps with petroleum jelly. When the cover is completely dry, treat the outside with a UV inhibitor spray. This will also restore the water-repellency of the material and greatly increases the life of the cover.

Created On: 09/17/2025